

# LET'S GET STARTED

Please review this guide carefully prior to installation for tips, tricks and a map to your new City Turn™ car seat. For further information, reference the instruction manual.



baby jogger®

PKG0001381133A

# GETTING TO KNOW YOUR SEAT





- 1 HEADREST/HARNESS ADJUSTMENT LEVER
- 2 ROTATION LEVER
- 3 LOWER ANCHOR STORAGE
- 4 FORWARD-FACING BELT PATH
- 5 TETHER
- 6 INSTRUCTION MANUAL STORAGE
- 7 RECLINE FOOT
- 8 RECLINE LEVER
- 9 FORWARD-FACING RAPIDLOCK
- 10 CUPHOLDER
- 11 REAR-FACING LEVEL INDICATOR
- 12 REAR-FACING RAPIDLOCK
- 13 REAR-FACING BELT PATH

# REAR-FACING INSTALLATION

For children 4-50 lb (1.8-22 kg)


Instructions for installing using your **vehicle's seat belt**.

**1.** Confirm your recline foot is in the rear-facing position by checking the label on the side of the foot. If it is not, rotate the recline foot located at the base of the seat to the rear-facing position. The recline foot is secure when it **'CLICKS'** into place.



**5.** Route both vehicle lap and shoulder belt under the rear-facing belt guides and RAPIDLOCK arm.


**2.** Adjust recline foot between positions 1-3 by squeezing the recline lever and lifting the base to extend/retract the foot. Check that the recline foot touches vehicle seat and level indicator is in the correct blue zone.



**6.** Buckle, then pull up on the shoulder belt to tighten and then buckle. Close the rear-facing RAPIDLOCK arm until you hear **'CLICK'**. **Note:** Do not pull on the belt with excessive force. If the belt is too tight, you will not be able to close the RAPIDLOCK. Do not lock the seat belt.



**For children over 40 lb (18 kg), MUST use recline position 1.**

**3.** Squeeze rotation lever at the front of the car seat and rotate the seat to expose the rear-facing belt path.



**7.** Rotate the seat back into place until you hear **'CLICK'** and confirm it is locked by pushing the seat side-to-side at belt path.

**4.** Open the rear-facing RAPIDLOCK arm.



**8.** Verify the level indicator has not changed.



**TIP:** The American Academy of Pediatrics recommends your child ride rear-facing as long as possible, to the upper weight or height limit allowed by your car seat.

# FORWARD-FACING INSTALLATION

For children 22-65 lb (10-30 kg), 49" or less



Instructions for installing using your vehicle's **seat belt and tether**.

**1.** Confirm your recline foot is in the forward-facing position by checking the label on the side of the foot. If it is not, rotate the recline foot located at the base of the seat to the forward-facing position. The recline foot is secure when it **'CLICKS'** into place.





**6.** Route seat belt through the forward-facing belt path.

**2.** Adjust the recline foot between positions 1-3 by squeezing the recline lever and lifting the base to extend/retract the foot. **For children 40-65 lb (18-30 kg), MUST use recline position 1. For children less than 40 lb (18 kg), MUST use recline position 3.**





**7.** Route seat belt behind RAPIDLOCK arm.

**3.** Raise headrest to the highest position to clear the forward-facing belt path.





**8.** Buckle, then remove vehicle belt slack by pressing down firmly in the center of the car seat and **Note:** Do not pull on the belt with excessive force. If the belt is too tight, you will not be able to close the RAPIDLOCK. Do not lock the seat belt.

**4.** Remove tether from back of seat and lay it over the front of the seat.



**9.** Close the forward-facing RAPIDLOCK arm until you hear **'CLICK'**.

**5.** Lift seat pad up and open the forward-facing RAPIDLOCK arm.



**10.** Locate your vehicle's tether anchor per your vehicle's instruction manual. Attach and tighten the tether.

See page 21 in the Installation Manual for additional Rear-Facing installation instructions.  
See page 28-33 in the Installation Manual for Rear-Facing with **LOWER ANCHOR ATTACHMENT** instructions.

See page 34 in the Installation Manual for additional Forward-Facing installation instructions.  
See page 40-45 in the Installation Manual for Forward-Facing with **LATCH** instructions.

# INSTALLATION CHECKLIST

See page 21 in the Installation Manual for complete installation instructions

- READ YOUR MANUAL.**  
Always read your car seat manual prior to installing your car seat. Your car seat manufacturer should be your primary resource for information regarding your car seat.
  
- INSTALLATION SHOULD BE TIGHT.**  
Car seats should not move more than 1" (2.5 cm) at the belt path.
  
- CHECK THE LEVEL INDICATOR IN REAR-FACING MODE.**
  
- PLACE CHEST CLIP AT ARMPIT LEVEL.**  
Not too high or too low.
  
- CHECK HARNESS HEIGHT.**  
*REAR-FACING:* Harness straps should be at or below the child's shoulders.  
*FORWARD-FACING:* Harness straps should be at or above the child's shoulders.
  
- PERFORM THE PINCH TEST IN THE SHOULDER AREA TO MAKE SURE THE HARNESS IS TIGHT ENOUGH.**  
It is important that the harness is snug against your child's body.
  
- CHECK INSTALLATION OFTEN.**  
Regularly inspect your seat's installation to ensure it is still tight and secure.